

COLOR Company, s. r. o., Štúrova 1504, 018 41 Dubnica nad Váhom

SK – Certificate of conformity	C_{SK}
---------------------------------------	-----------------------

Undersigned representative

of the manufacturer: **COLOR Company, s. r. o., Štúrova 1504, 018 41 Dubnica nad Váhom**

of the workshop: **COLOR Company, s. r. o., Štúrova 1504, 018 41 Dubnica nad Váhom**

hereby declares that the product:

Water diluted varnish for floor covering **LIGNOLAK**

is in compliance with the provisions of the Act No. 90/1998 Coll. on constructional products as amended, if it is used and applied in accordance to the manufacturer instructions and the following standards are applied for the product:

Act No. 163/2001 Coll. on chemical substances and chemical preparations as amended Public notice of the Ministry of Economy of the SR No. 515/2001 Coll. on details of the safety data sheet contents STN 74 4507: 1981 Test methods of the floorings. Determination of the anti-sliding properties of the flooring surface

Within the initial test of the type the following properties relating to the basic requirements were verified:

Property	Declared value or class	Number of the test record and reference to the laboratory
Anti-sliding properties	The flooring finished by a painting meets the requirement of the standard STN 74 4507 ucr = 0,3, us>0,3; ud > 0,3	Record No. 802/0200/99 dated 29. 07. 1999 1)
release of pollutants into the environment	Check of the safety data sheet	Record No. 800/23/0322/05 dated 27. 12. 2005 1)

Within the initial test of the type the following properties relating to product identification were verified:

Property	Declared value or class	Number of the test record and reference to the laboratory
water resistance	The flooring finished by a painting meets the requirement of the standard STN 49 2120 after the water action without any visual changes	Tests record No. 803/0203/99 dated 03. 08. 1999 1)
migration of certain elements	The flooring finished by a painting meets the requirement of the standard STN EN 71-3 maximum migrated element in mg/kg Sb 60, As 25, B and 500, Cd 75, Cr 60, Pb 90, Hg 60, Se 500	Report on analysis No. 170-98 dated 16. 11. 1999 2)

Description of the product:

LIGNOLAK is a mixture of the copolymer acrylate and urethane dispersion and water with an addition of special additives. It is a milky coloured suspension with a content of the involatile components of min. 30% and the outlet time min. 25 s. It is designed for a surfacing of the wooden floorings in the interiors against the moisture and for preservation of their properties and extension of their durability.

Use in the construction:

The painting substance is suitable for the surfacing of the wooden floorings in the interiors against the moisture and for preservation of their properties and extension of their durability.

Names and addresses of the laboratories, which carried out the tests:

- 1) AO reg. Č. SK02 LIGNOTESTING, a. s., Technická 5, 821 04 Bratislava
- 2) Accredited testing laboratory, Račianska 71, Bratislava

Name: Ing. Dušan Buček



COLOR Company s.r.o.
Štúrova 1504
018 41 Dubnica nad Váhom
IČO: 36 307 262
DIČ: SK 2020115020

Date: 3. 1. 2006